

PP1300

GLOSSY PAPER LABEL

Description

Glossy Inkjet paper, cast coated with excellent ink absorption. Vibrant color print-out on dye based and pigmented inks.

Material	Paper
Finishing	Glossy
Color	White
Adhesive	Permanent (high adhesion)
Liner	White kraft liner

Physical data

Face material

Property	Value	Unit	Standard
Basis weight	86 ± 4	g/m ²	ISO 536
Thickness	102 ± 6	µm	ISO 534
Opacity	87 ± 3	%	ISO 2471
Stiffness MD	5 ± 3	mN	ISO 2493
Stiffness CD	2 ± 1	mN	ISO 2493
Smoothness	> 110	Sec.	ISO 5627
CIE Whiteness	155 ± 6		ISO 11475

Adhesive

ISEGA approved

Property	Value	Unit	Test method
Service temperature	-20 to 80	°C	Climate chamber
Application temperature	> 5	°C	On glass

Liner

Property	Value	Unit	Standard
Basis weight	62 ± 6	g/m ²	ISO 536
Thickness	51 ± 5	µm	ISO 534

Disclaimer:

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.