

PP1600V

REMOVABLE STICKY NOTES

Description

A matt white bi-oriented polypropylene film with an Inkjet top coating to give good printability. This top coating has been formulated to work with inkjet technologies.

Physical data

Face material

| | |
|-----------|-------------------------------------|
| Material | Polypropylene film with top coating |
| Finishing | Matt |
| Color | White |
| Weight | 46 gsm |
| Thickness | 60 micron |

Adhesive

| | |
|--------------------------|---|
| Type | Peeable, Acrylic |
| Minimum application temp | +15 °C |
| In service temp | -5 °C to +60 °C |
| Initial tack | Low |
| Ultimate adhesion | Low |
| Notes | Good long term removability from a wide variety of surfaces Complies with regulations for direct contact with dry, moist and such Kind of fatty foodstuffs which have a reduction factor of at least 2 According to EC directive 85/572/CEE (ISEGA certificate No. 30229 U 10) |

Release liner

| | |
|-----------|----------------|
| Weight | 80 gsm |
| Color | White glassine |
| Thickness | 68 micron |

Shelf life

1-2 years

Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.