

# TV-400

## CLEAR MATTE VINYL



### Description

TV-400 is a flexible top-coated clear matte vinyl film coated with a permanent pressure sensitive acrylic adhesive and backed with a kraft release liner. This product is generally used for application on cables and hoses because of its flexible properties.

### Physical data

		Typical value	Unit	Test method
<b>PVC film</b>	Thickness	80	Micron	ASTM D 3652
<b>Adhesive</b>	Thickness	22	Micron	ASTM D 3652
	Adhesion from:		N / 25 mm	FTM (72 hour dwell)
	- Stainless steel	18		
	- Glass	17		
	- Polypropylene	13		
	- Acrylic	20		
	Shear	50	Hours	FTM 8 (1 hour dwell on stainless steel with a 2kg weight)
	Probe tack	380	Gram / cm <sup>2</sup>	ASTM D 2979
<b>Liner</b>	Thickness	81	Micron	ASTM D 3652
<b>Complete construction</b>	Service temp	-40 to +80	°C	
	Application temp	2	°C	

### Storage

Material is stable for two years stored at max 21 °C and 50% relative humidity. Damp conditions, excessive heat and/or freezing conditions should be avoided.

### Additional information

The expected exterior/outdoor durability of this product is up to 5 years (dependent on longevity of substrate). Material meets REACH and RoHS requirements (2002/95/EC), IMDS data available upon request.

#### Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.