

KettleTag

GALVANIZING TAG

Description

The only galvanizing tags with text and barcodes that survive the entire galvanizing process

The American Galvanizer's Association lists 9 steps in the hot dip galvanizing process. Since 2001, the KettleTag has been surviving them all.

Attach one tag and you're done. KettleTag means you don't have to remove your metal tags before the acid dip, or remove your paper tags before the molten zinc bath. No removing; no reattaching.

- Increased efficiency for galvanizers.
- Traceability and error-proof installations for fabricators.
- Eliminates unsafe handling.
- Processes vary. Call for samples and test KettleTag in your process.

Physical data

Metal galvanizing
Galvanizers; Fabricators
Tracking work-pieces through the entire galvanizing process
1000°F (538°C) after removal of protective laminate
Tags legible after most caustic/acid rinses (10 minutes each) and molten zinc bath
Moderate Highly resistant to sunglight and fading
Width: 3.0 in (76 mm)
Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Lengths: 3.0 in (76 mm)
Metal, with high contrast

Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

ALTEC industrial identification nv / sa Zone Cargovil B60; Erasmuslaan 11 1804 Eppegem - Belgium Subscription Content of Content